

COMPONENTI MECCANICI
PER ASCENSORIMECHANICAL LIFT
COMPONENTSPARACADUTE PROGRESSIVO
BIDIREZIONALE BSG-25PBIDIRECTIONAL PROGRESSIVE
SAFETY GEARS BSG-25P

T.243

MODULO PER / FORM FOR

ORDINE / ORDER No. _____

RICH.D'OFFERTA / INQUIRY _____

DITTA / COMPANY _____


DATA / DATE _____

BSG-25P


MASSA DA ARRESTARE / MASS TO BE GRIPPED
F max (P+Q) (Kg)CARICO NOMINALE / NOMINAL LOAD
Q (Kg)VELOCITA' NOMINALE / RATED SPEED
V (m/s)VELOCITA' INTERVENZO / TRIPPING SPEED
V max (m/s)PARACADUTE / SAFETY GEARS
- fornitura base / basic supply = -
- fornitura con fissaggio tipo A / assembly type A = A
- fornitura con fissaggio tipo B / assembly type B = BTIPOLOGIA DI GUIDA / GUIDE TYPE
- trafilato / cold drawn = C
- lavorato / machined = MLUBRIFICAZIONE GUIDA / GUIDE LUBRICATION
- lubrificato / lubricated = L
- secco / dry = D-
A
BC
ML
D

ACCESSORI / OPTIONALS

ATTACCO FUNE LIMITATORE / ROPE HITCH

Tipo S:
Diametro fune
DG=6-6,5; 7-8;
9-11 mmTipo K:
Diametro fune
DG=6-6,5 mmType S:
Rope diameter
DG=6-6,5; 7-8;
9-11 mmTipo K:
Rope diameter
DG=6-6,5 mmS
KØ FUNE / ROPE Ø
6-6,5 mm
7-8 mm
9-11 mmPOSIZIONE FUNE LIMITATORE
GOVERNOR ROPE LOCATIONA
BLUNGH. ALBERO SINCRONIZZAZIONE / SYNCHRONIZATION SHAFT LENGHT
DBG (mm)CONTATTO PARACADUTE / SAFETY GEAR CONTACT
- riarmo automatico / self reset type = SR
- riarmo manuale / manual reset type = MRSR
MR

GUIDA / GUIDE RAILS



k (8-16 mm)

b (mm)

QUANTITA' / QUANTITY
(paia/pair)

COMMENTO / COMMENT